

IBM Infoprint 1332, Infoprint 1352, Infoprint 1372 and IBM MFP Options



Infoprint 1332



Infoprint 1372

Highlights

- **Delivers output at fast print speeds for exceptional productivity**
- **Offers a wide range of input and output options for increased flexibility**
- **Integrate easily with multi-function options**
- **Provide expert onsite printer repair from specially trained professionals**

To compete effectively in today's demanding business environment, businesses need affordable and reliable printing solutions. Designed for small, medium and large sized workgroups, the IBM Infoprint® 1332, Infoprint 1352 and Infoprint 1372 deliver fast print speeds, flexible connectivity and extensive input and output options to enable a scalable solution.

Enabling quick output and high-quality

The Infoprint 1332, Infoprint 1352 and Infoprint 1372 can help you achieve fast turnaround and help make your workgroup more productive with output delivery of up to 35, 40 and 45 ppm respectively. And all the printers provide 1200 x 1200 dots-per-inch (dpi) resolution for crisp text and high-quality graphics.

Consolidating IT hardware

By upgrading the Infoprint 1332, Infoprint 1352 and Infoprint 1372 with any one of the IBM M22, M26 and M30 MFP Options, you can consolidate full-function copy, fax and network scan capabilities, including fax from workstation, scan to e-mail and FTP on to one device. This can help leverage your IT investment and reduce device management time.

Relying on world-class service

With IBM service, you receive high-quality, reliable support from experts with a comprehensive knowledge of IBM printers, software and supplies. Next-day 9x5 and same-day 24x7 service offerings are available on all IBM printers in the US.

Printers at a glance	IBM Infoprint 1332	IBM Infoprint 1352	IBM Infoprint 1372
Maximum speed (up to)¹	35 ppm	40 ppm	45 ppm
First-page-out time (as fast as)¹	8.5 seconds	10 seconds	8.5 seconds
Technology/processor	Monochrome laser/300 MHz	Monochrome laser/350 MHz	Monochrome laser/500 MHz
Maximum monthly usage²	175,000 pages	200,000 pages	225,000 pages
Print resolution	300, 600, 1200 image quality; 1200 dpi at a slower speed (1332, 1352, 1372)		
Models	Base, network (n)	Base, network (n)	Base, network (n)
Memory (std/max)	32/288 MB (base) 64/320 MB (n)	64/320 MB (base) 64/320 MB (n)	64/320 MB (base) 80/336 MB (n)
Paper handling³	Duplex (optional)	Duplex (optional)	Duplex (optional)
Standard/max input capacity	350/3,850	600/4,100	600/4,100
Input options	Up to four additional drawers: 250-, 400-, 500- and 2,000-sheet drawers available. Only one 2,000-sheet drawer can be installed (1332, 1352, 1372)		
Standard/max output capacity	250/2,750	500/3,000	500/3,000
Output options	Up to three of the following output options (1332, 1352, 1372): output expander (up to 650 sheets); StapleSmart Finisher (up to 750 sheets unstapled, 600 sheets stapled); high-capacity output stacker (up to 1,850 sheets); five-bin mailbox (up to 100 sheets per bin; not compatible with 1332)		
Standard datastreams	PostScript Level 3 emulation, PCL6 emulation, PDF v1.2, PDF v1.3 and PPDS (1332, 1352, 1372)		
Application solutions	IPDS, ImageQuick, Optra Forms, Bar Code Card, Decryption Card (1332, 1352, 1372)		
Printer attachments (standard)	USB port, bidirectional parallel port (base); USB port, Ethernet 10BaseT/100BaseTX (n) (1332, 1352, 1372)		
Optional internal	Ethernet 10/100 BaseTX; Token Ring; Twinax/Coax adapter for SCS; Serial; Parallel (1332, 1352, 1372)		
Optional external	Ethernet; Token Ring; Serial adapter; Wireless Ethernet (802.11b) and Bluetooth (1332, 1352, 1372)		
Media	Sizes: letter, legal, executive, folio, statement, A4, A5, JIS B5, universal and several envelopes (1332, 1352, 1372) Types: paper, cardstock, transparencies, paper labels and envelopes (1332, 1352, 1372) Weights: plain paper: 16 to 47 lb bond (60 to 176 g/m ²) (1332, 1352, 1372)		
Physical characteristics	16.6" (W) x 19.6" (D) x 13.6" (H)	17.2" (W) x 20.2" (D) x 16" (H)	17.2" (W) x 20.2" (D) x 16" (H)
Weight	38 lbs	41.5 lbs	41.5 lbs
Toner yield⁴	Starter: 21K After: 5K, 21K	Starter: 21K After: 5K, 21K, 32K	Starter: 21K After: 5K, 21K, 32K
Cost-saving features	IBM return program print cartridges; high-yield print cartridges; optional duplex printing; toner darkness settings offer up to 50% toner savings (1332, 1352, 1372)		
Warranty	One year, Depot Exchange (upgrades are available) (1332, 1352, 1372) For more information, see ibm.com/support/warranties/us		

For expanded specifications, visit: ibm.com/printers/workgroup

¹ Exact speed varies depending on document complexity, system configuration, software application, driver and printer state.

² IBM does not recommend printing this monthly maximum on a consistent basis.

³ Printer stands are available for improved stability.

⁴ Assumes 5% toner coverage per page. Toner yields are provided for planning purposes and are not a guarantee of minimum life; actual yields may vary.



MFP Options at a glance	IBM M22	IBM M26	IBM M30 ¹
Document handling			
ADF (capacity/max speed ²)	25 sheets/15 ipm letter black 14 ipm letter color	50 sheets/23 ipm letter black 14 ipm letter color	50 sheets/23 ipm letter black 14 ipm letter color
Console type	LCD	LCD	Touchscreen
Maximum scan size	Legal (8.5" x 14")	Legal (8.5" x 14")	Legal (8.5" x 14")
Input	Simplex	Duplex (single pass)	Duplex (single pass)
Scanning capabilities			
Scan file formats	JPEG, TIFF, PDF, PostScript	JPEG, TIFF, PDF, PostScript	JPEG, TIFF, PDF, PostScript
Type	Color and monochrome	Color and monochrome	Color and monochrome
Maximum optical resolution	600 x 600 dpi	600 x 600 dpi	300 x 300 dpi
Scan destinations/archiving	FTP server, workstation, e-mail	FTP server, workstation, e-mail	FTP server, workstation, e-mail
Fax capabilities			
Maximum fax resolution	400 x 400 dpi	400 x 400 dpi	400 x 400 dpi
Modem speed	33.6 Kbps	33.6 Kbps	33.6 Kbps
Receive fax	Yes	Yes	Yes
Send hard copy fax	Platen or automatic document feeder	Platen or automatic document feeder	Platen or automatic document feeder
Send soft copy fax	From PostScript 3 print driver at workstation	From PostScript 3 print driver at workstation	From PostScript 3 print driver at workstation
Memory send	Yes	Yes	Yes
Internal faxing (scan to FTP)	Yes	Yes	Yes
Fax-server integration	Biscom, Equisys, Omtool, RightFax	Biscom, Equisys, Omtool, RightFax	Biscom, Equisys, Omtool, RightFax
Physical characteristics³	19.6" (W) x 14.4" (D) x 10.8" (H)	22.4" (W) x 16.9" (D) x 7.5" (H)	33" (W) x 21.5" (D) x 12" (H)
Weight	11.8 lbs	15.4 lbs	26 lbs
Warranty	One year, Depot Exchange (upgrades are available) For more information, see ibm.com/support/warranties/us	One year, Depot Exchange (upgrades are available)	One year, next-day IBM onsite repair (upgrades are available)

¹ The M30 requires a network model IBM Infoprint 1332, Infoprint 1352 or Infoprint 1372.

² Exact scan speed varies depending on the document attributes, system configuration and user selected settings.

³ MFP furniture and printer stands are available for improved stability.



Improve processing time and create a scalable output solution by upgrading the IBM Infoprint 1352 with the IBM M26 MFP Option.

For more information

To learn more about the IBM Infoprint 1332, 1352, and 1372 as well as the M22, M26 and M30 MFP Options, visit ibm.com/printers or call 1-800-4-YOU (426-4968).



© Copyright IBM Corporation 2003

IBM Printer Outlet.com
1-866-430-6202

Printed in the United States of America

04-03

All Rights Reserved

IBM, the IBM logo, the e-business logo, Infoprint, Intelligent Printer Data Stream and IPDS are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both.

Adobe and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Other company, product and service names may be trademarks or service marks of others.

References in this publication to IBM products or services do not imply that IBM intends to make them available in all countries in which IBM operates.

IBM hardware products are manufactured from new parts, or new and used parts. In some cases, the hardware product may not be new and may have been previously installed. Regardless, our warranty terms apply.

IBM Printer Outlet.Com
1-866-430-6202

Fax for a Quick Quote
817-430-6250

#1352

Organization _____

Name _____

Phone _____ **Fax number** _____
(area code) (area code)

E-mail _____

Address _____

City _____ **State** _____ **Zip** _____

Please indicate your specifications or requirements:

Additional comments:
